

NORDIC RACING OIL 5W/50

Fully Synthetic Passenger Car Motor Oil

NORDIC RACING OIL 5W/50 is a high-performance motor oil based on 100% synthetic technology with exceptional quality, delivering extreme performance in gasoline-, diesel- and LPG fuelled engines in passenger cars with or without turbocharger, working under severe temperature and load conditions.

NORDIC RACING OIL 5W/50 is based on high quality synthetic base oil in combination with an unique additive package to ensure the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersant and detergent properties.
- Excellent cold temperature properties for a smooth cold start.
- Excellent protection against wear, corrosion and foam.
- Suited for extreme and severe conditions.

NORDIC RACING OIL 5W/50 exceeds the following performance criteria:

API SN/CF	ACEA A3/B4	MB 229.3
Porsche A40	BMW LL-01	VW 502.00/505.00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W/50
Density @15°C	kg/m ³	ASTM 4052	859
Kinematic Viscosity @ 40°C	mm ² /s	ASTM D7042	110
Kinematic Viscosity @ 100°C	mm ² /s	ASTM D7042	17.8
Viscosity Index		ASTM D2270	180
Viscosity CCS @ -30, max	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	10
Sulphated Ash	%Wt	ASTM D874	1.16

Date Issued: 14-06-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------