

## NORDIC FUELTEC 0W20 SP

Fully Synthetic Passenger Car Motor Oil

**NORDIC FUELTEC 0W/20 SP** is the advanced synthetic energy conserving motor oil specially developed for the most modern high output gasoline and turbocharged engines in passenger cars, sport utility vehicles and light-duty trucks, operating on ethanol- containing fuels up to E85. It is formulated to help improve & retain fuel economy and protect vehicle emission system & turbocharger components while meeting the latest GM Dexos1<sup>TM</sup> demands.

**NORDIC FUELTEC 0W/20 SP** is based on exceptional quality synthetic base oil in combination with a special selected additive package to reach to following properties:

- Improved protection against stochastic pre-ignition
- Improving sludge protection, piston cleanliness, turbo-charger protection, seal compatibility, wear protection.
- Special friction modifiers used in this Energy conserving oil help improving & retaining fuel economy.
- Offers excellent lubrication at low temperatures and protect engine at high temperatures.
- Superior volatility characteristics reduce oil consumption and hydro-carbon pollution (VOCs).
- Advanced additive chemistry helps in emission system durability.
- Compatible with ethanol-containing fuels up to E85.

**NORDIC FUELTEC 0W20 SN/RC** exceeds the following performance criteria:

GM Dexos1<sup>TM</sup>:2015

ILSAC GF-5

API SN + RC + SP

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	0W/20
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	846
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	46.9
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	8.9
Viscosity Index		ASTM D2270	174
Viscosity CCS -35°C, max	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-47
Total Base Number	mgKOH/g	ASTM D2896	7.9
Date Issued: 24-04-2021	Supersedes:	Revision Nr.: 1	