

NORDIC FUELTEC 0W/20 LL

Fully Synthetic Fuel Economy Passenger Car Motor Oil

NORDIC FUELTEC 0W/20 LL is a fully synthetic fuel saving long life oil based for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 508.00/509.00 has been prescribed.

Remark: This product is not backwards compatible with older vehicles that require the VW 504 00/507 00 specification.

NORDIC FUELTEC 0W/20 LL is formulated with high quality 100% Poly Alpha Olefin (PAO) base stocks in combination with a unique additive technology to achieve the following performance:

- Exceptional good low temperature properties.
- Excellent protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Improved fuel economy

NORDIC FUELTEC 0W/20 LL exceeds the following performance criteria:

VW 508 00/509 00

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	0W/20
Density @15°C	kg/m ³	ASTM D4052	835
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	39
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.8
Viscosity Index		ASTM D2270	177
Viscosity CCS @-35°, max.	cP	ASTM D5293	328
Flash Point COC	°C	ASTM D92	>205
Pour Point	°C	ASTM D97	-45
Total Base Number	mgKOH/g	ASTM D2896	6.7
Sulphated Ash	%Wt	ASTM D874	0.8

Date Issued: 29-05-2021

Supersedes:

Revision Nr.:1