

NORDIC EVOTECH 5W/30 C3

Fully Synthetic MID SAPS Passenger Car Motor Oil

NORDIC EVOTECH 5W/30 C3 is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger cars and light vans with or without turbocharger. **NORDIC EVOTECH 5W/30 C3** is developed for use in engine which are equipped with or without an exhaust gas after treatment system.

NORDIC EVOTECH 5W/30 C3 is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- MID SAPS technology.
- Good protection against wear, foam en corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.

NORDIC EVOTECH 5W/30 C3 exceeds the following performance criteria:

Exceeds	ACEA C3 Dexos 2	API SN/CF BMW LL-04	Renault RN 0700 MB-229.51
----------------	--------------------	------------------------	------------------------------

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W/30
Density @15°C	kg/m ³	ASTM D4052	850
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	65
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	11.7
Viscosity Index		ASTM D2270	175
Viscosity CCS @-30°, max.	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>218
Pour Point	°C	ASTM D7346	-39
Total Base Number	mgKOH/g	ASTM D2896	7.6
Sulphated Ash	%Wt	ASTM D874	0.8

Date Issued: 29-05-2021

Supersedes:

Revision Nr.: 1

Nordic Lube ApS, Udsigten 19, 3500 Værleose, Denmark

www.nordic-lube.com