

NORDIC EVOTECH 5W/30 C2/C3

Fully Synthetic MID SAPS Passenger Car Motor Oil

NORDIC EVOTECH 5W/30 C2/C3 is a high performance fuel saving mid SAPS engine oil based on 100% synthetic technology for use in the latest generation gasoline and diesel engines of passenger car and light vans with or without turbocharger. **NORDIC EVOTECH 5W/30 C2/C3** is developed for use in engine which are equipped with or without an exhaust gas after treatment system.

NORDIC EVOTECH 5W/30 C2/C3 is based on high performance 100% synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- mid SAPS technology.
- Good protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Equipped for diesel engines with an exhaust after treatment system.
- Fuel saving properties.
- Excellent detergency and dispersency properties.

NORDIC EVOTECH 5W/30 C2/C3 exceeds the following performance criteria:

Exceeds	API SN MB-229.52	Dexos 2	ACEA C2/C3-12
----------------	---------------------	---------	---------------

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m ³	ASTM D4052	854
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	72
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.1
Viscosity Index		ASTM D2270	165
Viscosity CCS @-30°, max.	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>218
Pour Point	°C	ASTM D97	-36
Total Base Number	mgKOH/g	ASTM D2896	7.0
Sulphated Ash	%Wt	ASTM D874	0.78

Date Issued: 29-05-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------