

NORDIC VECTRO 10W/40

Semi synthetic passenger car motor oil

NORDIC VECTRO 10W/40 is an universal high performance fuel saving synthetic oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for engines equipped with a Particulate Filter.

NORDIC VECTRO 10W/40 is formulated with high quality synthetic base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

NORDIC VECTRO 10W/40 exceeds the following performance criteria:

ACEA A3/B4-16			
API SN	MB-229.3		
MB 226.5	MB 229.1		RN 0700/0710
VW 501.01/505.00			

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W/40
Density @15°C	kg/m ³	ASTM D4052	862
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	91.1
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	155
Viscosity CCS @-25°, max.	cP	ASTM D5293	<700
Flash Point COC, min	°C	ASTM D92	>215
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	10.1
Sulphated Ash	%Wt	ASTM D874	1.22

Date Issued: 14-06-2021

Supersedes:

Revision Nr.: 1