

NORDIC EVOTECH 0W/30 C2

High Performance Passenger Car Engine Oil

NORDIC EVOTECH 0W/30 C2 is a very high-performance fuel saving oil based on Synthetic technology for use in the very latest gasoline and diesel engines of passenger cars equipped with exhaust particle filters. Designed to meet the requirements for the new Ford M2C950-A specification for diesel engines. Also suitable for the latest Peugeot/Citroën vehicles that require PSA B71 2312.

NORDIC EVOTECH 0W/30 C2 is formulated with high quality synthetic base stocks in combination with special selected additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Excellent high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- Excellent dispersancy and detergency level.
- Very high viscosity index.

NORDIC EVOTECH 0W/30 C2 exceeds the following performance criteria:

ACEA C2

Ford M2C950-A

PSA B71 2312

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	0W/30
Density @15°C	kg/m ³	ASTM D4052	843
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	45.5
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9.5
Viscosity Index		ASTM D2270	201
Viscosity CCS @-35°, max.	cP	ASTM D5293	6200
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-42
Total Base Number	mgKOH/g	ASTM D2896	7.8
Sulphated Ash	%Wt	ASTM D874	0.79

Date Issued: 29-05-2021

Supersedes:

Revision Nr.: 1