

NORDIC VECTRO 20W/50

Heavy Duty Diesel Engine Oil

NORDIC VECTRO 20W/50 is an extra high performance universal engine oil designed for high loaded diesel engines in light- and heavy commercial vehicles working under severe operating conditions through the whole year for use in Euro-3, Euro-4 and Euro-5 engines equipped with EGR and/or SCR. This product is not suitable for vehicles equipped with DPF filters.

NORDIC VECTRO 20W/50 is formulated with high refined solvent mineral base stock in combination with a special additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals possible.

NORDIC VECTRO 20W/50 meets the following performance criteria:

API CI-4	API SL	ACEA E7	MB 228.3
MAN M 3275	Volvo VDS-3	Deutz DQC-III	MTU Type 2
Mack EO-N	Cummins CES 20077/20078	Caterpillar ECF-1a	Renault RLD-2
DDC 93K215	JASO DH-1	Global DHD-1	

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	20W/50
Density @15°C	kg/m ³	ASTM D4052	890
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	138.3
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	17.7
Viscosity Index		ASTM D2270	141
Viscosity CCS @-15°, max.	cP	ASTM D5293	9500
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-24
Total Base Number	mgKOH/g	ASTM D2896	12.2
Sulphated Ash	%Wt	ASTM D874	1.5

Date Issued: 06-05-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------