

## NORDIC MOTOR OIL SAE 30 CF

### Mineral Heavy Duty Diesel Engine Oil

**NORDIC MOTOR OIL SAE 30 CF** is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions.

**NORDIC MOTOR OIL SAE 30 CF** is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended.

**NORDIC MOTOR OIL SAE 30 CF** is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

**NORDIC MOTOR OIL SAE 30 CF** exceeds the following performance criteria:

API SG/CF

MTU Type 2

CCMC G2/D1

MIL-L-46152

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	30
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	893
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	104.5
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	11.5
Viscosity Index		ASTM D2270	99
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-27
Total Base Number	mgKOH/g	ASTM D2896	12.5

Date Issued: 24-04-2021

Supersedes:

Revision Nr.: 1