

NORDIC MOTOR OIL SAE 40 CF

Mineral Heavy Duty Diesel Engine Oil

NORDIC MOTOR OIL SAE 40 CF is a heavy duty diesel engine oil developed to meet the requirements of a variety of diesel engines operating under severe conditions.

NORDIC MOTOR OIL SAE 40 CF is suitable for use in a wide range of on- and off-highway applications where an API CF oil is recommended.

NORDIC MOTOR OIL SAE 40 CF is based on high quality refined virgin base oil in combination with a special additive package to ensure the following properties:

- High thermal and oxidation stability.
- Effective in preventing from wear, corrosion and foam.
- High dispersancy and detergency properties.

NORDIC MOTOR OIL SAE 40 CF exceeds the following performance criteria:

API SG/CF

MTU Type 2

CCMC G2/D1

MIL-L-46152

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	40
Density @15°C	kg/m ³	ASTM D4052	897
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	134
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.6
Viscosity Index		ASTM D2270	97
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-21
Total Base Number	mgKOH/g	ASTM D2896	12.5

Date Issued: 24-04-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------