

NORDIC VECTRO 80W/90 GL4

Automotive mineral Gear Oil EP 80W/90

NORDIC VECTRO 80W/90 GL4 is an universal high performance mineral EP gear oil for use in manual transmission en transaxles of passenger cars, vans, light- and heavy commercial vehicles, off-highway equipment, mining and agriculture where a SAE 80W-90 GL-4 is been required.

NORDIC VECTRO 80W/90 GL4 is formulated with high refined mineral base stocks in combination with a special EP-additive technology to achieve the following performance:

- Good Extreme Pressure and Antiwear properties.
- High thermal- and oxidation stability.
- Effective rust, wear and corrosion protection.
- Better low temperature provides easy start-up at low ambient temperatures.
- Good anti-foam properties ensure film strength for effective lubrication.
- Excellent seal compatibility.

NORDIC VECTRO 80W/90 GL4 exceeds the following performance criteria:

API GL-4

MIL-L-2105

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J306	80W/90
Density @15°C	kg/m ³	ASTM D4052	893
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	142
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	14.3
Viscosity Index		ASTM D2270	96
Viscosity Brookfield @-26°C	cP	ASTM D5293	150000
Flash Point COC, min	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-24

Date Issued: 06-05-2021

Supersedes:

Revision Nr.: 1