

## NORDIC VECTRO 85W/90 GL5

### Automotive Gear Oil

**NORDIC VECTRO 85W/90 GL5** is a high performance differential lubricant designed to provide excellent lubrication in a wide range of drive trains of light & heavy duty commercial vehicles.

**NORDIC VECTRO 85W/90 GL5** is based on high quality mineral base oil in combination with a special additive package to ensure the following properties:

- Good thermo-oxidative stability.
- Good load bearing characteristics.
- Effective rust and corrosion protection.
- High low temperature fluidity provides smoother shifting at low ambient temperatures.
- Exceptional shear stable.

**NORDIC VECTRO 85W/90 GL5** exceeds the following performance criteria:

API GL-5	MB 235.0	MAN 342-M1	MIL-L-2105D
Volvo 97310	Volvo 97316	Voith 3.325-339	
ZF TE-ML 07A/08/16B/16C/16D/17B/19B/21A			

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	85W/90
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	901
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	158
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	15.2
Viscosity Index		ASTM D2270	96
Brookfield Viscosity @-40°C	cP	ASTM D2983	150000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-24

Date Issued: 06-05-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------