

NORDIC VECTRO ATF D II

Automatic Transmission Fluid

NORDIC VECTRO ATF D II is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger cars, light vans and commercial vehicles.

NORDIC VECTRO ATF D II is formulated on high quality re-refined mineral- and synthetic base oil in combination with an unique additive package to reach the following properties:

- Good thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against corrosion, foam and wear.

NORDIC VECTRO ATF D II meets the following performance criteria:

GM Dexron II-D
Voith H55.6335.xx

MAN 339 type V1
ZF TE-ML 03D/04D/14A/17C

MAN 339 type Z1

MB 236.9

Typical Analysis

Properties	Unit	Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m ³	ASTM D4052	855
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	35.2
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.2
Viscosity Index		ASTM D2270	172
Viscosity Brookfield @-40°, max.	cP	ASTM D2983	50.000
Flash Point COC	°C	ASTM D92	172
Pour Point	°C	ASTM D7346	-48

Date Issued: 06-05-2021

Supersedes:

Revision Nr.: 1