

NORDIC VECTRO ATF D III

Automatic Transmission Fluid

NORDIC VECTRO ATF D III is a high quality universal fluid to be used in automatic transmission, torque convertors and power steering of passenger car, light vans and commercial vehicles.

NORDIC VECTRO ATF D III is formulated on high refined solvent mineral and synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very high viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

NORDIC VECTRO ATF D III meets the following performance criteria:

DEXRON IIIIF/G/H	Allison C4	CAT T0-2	MAN 339 Z1/Z2
MAN 339 V1/V2	MB 236.10/236.9/236.7/236.5/236.1		Voith 55.6335
Mercon	Volvo 97341	ZF 02F/03D/04D	ZF 11A/11B/14B/16L

Typical Analysis

Properties	Unit	Method	Typical Value
Color			Red
Density @15°C	kg/m ³	ASTM D4052	864
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	41
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	7.8
Viscosity Index		ASTM D2270	164
Viscosity Brookfield @-40°, max.	cP	ASTM D2983	<20000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-48

Date Issued: 06-05-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------