

NORDIC VECTRO ATF D VI

Automatic Transmission Fluid

NORDIC VECTRO ATF D VI is a high quality universal fluid based on 100% synthetic base stocks to be used in automatic transmission, torque convertors and powersteering of passenger car, light vans and commercial vehicles where a GM Dexron VI specification is required. **ATF Dexron VI** is backwards compatible where Dexron II and Dexron III is been required.

NORDIC VECTRO ATF D VI is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Verry high viscosity Index.
- Low pourpoint.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

NORDIC VECTRO ATF D VI exceeds the following performance criteria:

GM Dexron VI Voith 55.6335.3X (G607)

Typical Analysis

Properties	Unit	Method	Typical Value
Color			Red
Density @15°C	kg/m ³	ASTM D4052	846
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	29
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	5.9
Viscosity Index		ASTM D2270	152
Viscosity Brookfield @-40°, max.	cP	ASTM D5293	13000
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-48

Date Issued: 06-05-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------