

NORDIC STOU TRACTOR OIL 10W/40

Semi-synthetic STOU oil for agriculture and earth moving equipment.

NORDIC STOU TRACTOR OIL 10W/40 is a high quality universal semi-synthetic based so called "Super Tractor Oil Universal" (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particle Filter (DPF).

NORDIC STOU TRACTOR OIL 10W/40 is formulated on severely hydrocracked base stocks in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

NORDIC STOU TRACTOR OIL 10W/40 exceeds the following performance criteria:

Engine Spec	API CG-4/CF-4/CE/SF	MB 228.1	ACEA E3
UTTO/STOU Spec	JD J20C, J20D, J27	Ford M2C86B, 134D	Ford M2C159B
	Case MS 1204, 6, 7, 9	MF M 1135/1139/1143/1144/1145	
	CAT T0-2	API GL-4	Allison C4
	ZF TE-ML 06A, 06B, 06C, 06D, 06E, 06H 07B		NH 82009201, 2, 3
Hydr. Spec	Eaton M-2950S	Eaton I-280-S	Danfoss

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W-40
Density @15°C	kg/m ³	ASTM D4052	861
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	88
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	157
Viscosity CCS @-25°, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	10.6
SAE Grade		SAE J3000	10W-40