

## NORDIC STOU TRACTOR OIL 10W/30 STOU for agriculture and earth moving equipment

**NORDIC STOU TRACTOR OIL 10W/30** is a high-quality universal mineral based so called "Super Tractor Oil Universal" (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed "wet brakes". This product cannot be used in diesel engines equipped with a Diesel Particulate Filter (DPF).

**NORDIC STOU TRACTOR OIL 10W/30** is formulated on high refined solvent mineral base stock in combination with an unique additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

**NORDIC UTTO TRACTOR OIL SYN 80W** exceeds the following performance criteria:

<b>Engine Spec:</b>	API CG-4/CF-4/CE/SF	MB 227.1	ACEA E3
<b>STOU/UTTO Spec</b>	ZF TE-ML 06B,C,R,07B	Ford M2C159B/C	MF M 1145
	JD J27, J20C/D	Ford M2C86B/C	Ford M2C134D
	Case MS 1204/6/7/9	MF M 1135/ 1139	MF M 1143/1144
	Caterpillar TO-2	API GL-4	Allison C-4
	CNH MAT 3525,3526	NH 030C	NH 024C
	NH 82009201	NH 410B	NH 420A
<b>Hydr. Spec:</b>	Eaton M-2950S	Eaton I-280-S	Danfoss

### Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	10W-30
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	873
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	65.4
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	10.4
Viscosity Index		ASTM D2270	148
Viscosity CCS @-25°	cP	ASTM D5293	5500
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	10.9
SAE Grade		SAE J300	10W-30
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	873