

## NORDIC STOU TRACTOR OIL 15W/40

### STOU Oil for agriculture and earth moving equipment

**NORDIC STOU TRACTOR OIL 15W-40** is a high quality universal mineral based so called “Super Tractor Oil Universal” (STOU) developed for use in tractors, combines, harvesters and off the road equipment with or without turbocharger diesel engines. Super Tractor Oil Universal is also designed to lubricate the transmission, power take-off, final drive, hydraulic system and oil immersed “wet brakes”. This product cannot be used in diesel engines equipped with a Diesel Particle Filter (DPF).

**NORDIC STOU TRACTOR OIL 15W-40** is formulated on high refined solvent mineral base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

**NORDIC STOU TRACTOR OIL 15W-40** exceeds the following performance criteria:

<b>Engine Spec</b>	API CF-4/CE/SF	MB 227.1	ACEA E3
<b>UTTO/STOU Spec</b>	JD J20C/D	Ford M2C86B/C	Ford M2C 134D
	Case MS 1204/6/7/9	MF M 1135/1139	MF M 1143/1145
	Cat T0-2	API GL-4	Allison C-4
<b>Hydr. Spec</b>	Eaton M-2950S	Eaton I-280-S	Danfoss

## Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	15W-40
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	882
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	102
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	13.8
Viscosity Index		ASTM D2270	139
Viscosity CCS @-25°, max.	cP	ASTM D5293	7000
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-36
Total Base Number	mgKOH/g	ASTM D2896	10.7
Sulphated Ash	%Wt	ASTM D874	1.38

Date Issued: 12-10-2015	Supersedes: 23-03-2012	Revision Nr.: 1
-------------------------	------------------------	-----------------