

NORDIC UTTO TRACTOR OIL 85W

UTTO oil for agriculture and off-road applications

NORDIC UTTO TRACTOR OIL 85W is a high quality universal mineral so called “Universal Tractor Transmission Oil” (UTTO) developed is suitable for modern high performance agriculture application require a single lubricant for transmission, differential, power take-off, hydraulic system and oil “wet” brakes. **This product cannot be used as lubricant for the engine.**

NORDIC UTTO TRACTOR OIL 85W is formulated on high refined solvent mineral base stocks in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- Excellent cold start properties.
- High anti-foam, anti-wear and anti-corrosion properties.
- Suitable for Wet Brakes.

NORDIC UTTO TRACTOR OIL 85W exceeds the following performance criteria:

| | | | |
|--------------------|----------------|---------------|----------------|
| API GL-4 | JD JDC20C, 20D | Ford M2C86B/C | Ford M2c 134D |
| Case MS 1204/6/7/9 | Mat 3525/3526 | MF M1135/1143 | MF M1145 |
| Cat TO-2 | Volvo WB101 | Allison C4 | JCMAS HK P-041 |
| Eaton M-2950S | Eaton I-280-S | Sauer Danfoss | |

Typical Analysis

| Properties | Unit | Method | Typical Value |
|-----------------------|--------------------|------------|---------------|
| SAE Grade | | SAE J3000 | 85W |
| Density @15°C | kg/m ³ | ASTM D4052 | 884 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 72 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 11.5 |
| Viscosity Index | | ASTM D2270 | 157 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D97 | -30 |
| Total Base Number | mgKOH/g | ASTM D2896 | 8.6 |
| Sulphated Ash | %Wt | ASTM 874 | 1.34 |

Date Issued: 06-05-2021

Supersedes:

Revision Nr.: 1