

## NORDIC EP GEAR OIL ISO 68

### Mineral Industrial Gear Oil

**NORDIC EP GEAR OIL ISO 68** is a high performance extreme pressure gear oils developed for lubrication of heavy duty industrial gears working under severe operating conditions.

**NORDIC EP GEAR OIL ISO 68** is based on high quality mineral base oil in combination with an unique additive package to ensure the following properties:

- Excellent load carrying capability protects gears against scuffing and wear and offers long equipment life and reduced maintenance costs.
- High thermo-oxidative stability helps resist deposit formation, provides enhanced system cleanliness and enables longer service intervals.
- Provides effective rust and corrosion protection to all gearbox components.
- Excellent demulsibility property enables trouble-free operation in conditions encountering water/ moisture.

### NORDIC EP GEAR OIL ISO 68

exceeds the following performance criteria:

DIN 51517-3 CLP

ISO 12925-1 CKC

AGMA 9005 E-02

US Steel 224

David Brown S1.53.101

### Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade		ISO 3448	68
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	884
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	68.2
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	8.7
Viscosity Index		ASTM D2270	98
Flash Point COC, min	°C	ASTM D92	201
Pour Point	°C	ASTM D7346	-15
FZG Fail Load Stage, min		DIN 51354-2	>12
Total Acid Number	mgKOH/g	ASTM D664	<0.5

Date Issued: 12-04-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------