

**NORDIC ELEVATOR OIL 46** is a universal high-performance lubricant specially designed for the lubrication of hydraulic lifts and elevators for both indoor and outdoor use.

**NORDIC ELEVATOR OIL 46** is based on high quality mineral virgin base oil in combination with a special additive to ensure the following properties.

- Excellent stick-slip properties.
- Very good anti-wear, anti-rust and anti-foam properties.
- High oxidation stability.
- Good resistance to high pressure and loads.
- Excellent demulsification properties.
- Good filterability.
- Strong adhesion to (vertical) slides

**NORDIC ELEVATOR OIL 46** exceeds the following performance criteria:

DIN 51524 Part II (HLP)    ISO 11158 HM    AFNOR NFE 48-603 HM  
DIN 51502 CGLP

### Typical Analysis

Properties	Unit	Method	Typical Value
ISO VG Grade			46
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	875
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	49.
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	8.7
Viscosity Index		ASTM D2270	157
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-39
FZG Fail Load Stage, min		DIN 51354-2	12
Total Acid Number	mgKOH/g	ASTM D974	0.5