

NORDIC PERMANENT 10W/40 SL/CF

Synthetic technology Passenger Car Motor Oil

NORDIC PERMANENT 10W/40 SL/CF is an universal high performance synthetic technology oil for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particle Filter (DPF).

NORDIC PERMANENT 10W/40 SL/CF

is formulated with high quality re-refined base stocks in combination with a special additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.

NORDIC PERMANENT 10W/40 SL/CF exceeds the following performance criteria:

API SL/CF MB229.1 VW 501.01

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	10W/40
Density @15°C	kg/m ³	ASTM D4052	865
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	90
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	13.9
Viscosity Index		ASTM D2270	156
Viscosity CCS @-25°, max.	cP	ASTM D5293	700
Flash Point COC, min	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-39
Total Base Number	mgKOH/g	ASTM D2896	6.4
Sulphated Ash	%Wt	ASTM D874	0.95

Date Issued: 14-06-2021	Supersedes:	Revision Nr.: 1
-------------------------	-------------	-----------------