

NORDIC VECTRO 5W/30 LL

Fully Synthetic MID SAPS Passenger Car Motor Oil

NORDIC VECTRO 5W/30 LL is a high-performance fuel saving MID SAPS long life oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger cars and light vans where a VAG norm 504.00/507.00 has been prescribed and also suitable for vehicles where MB 229.51 and BMW LL-04 are required.

Remark: not suitable for R5- an V10 TDI engines and engines where VAG norm VW 506.01 is being advised.

NORDIC VECTRO 5W/30 LL is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Extended oil drain interval.
- Also suitable for engines equipped with other catalyst like TWC.

NORDIC VECTRO 5W/30 LL exceeds the following performance criteria:

ACEA C3 VW 504.00/507.00 MB 229.51 BMW LL-04
API SN

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W/30
Density @15°C	kg/m ³	ASTM D4052	856
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	71.0
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	12.0
Viscosity Index		ASTM D2270	166
Viscosity CCS @-30°, max.	cP	ASTM D5293	6600
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D	-42

Date Issued: 14-06-2021

Supersedes:

Revision Nr.: 1