

NORDIC EVOTECH 5W/30 C2

Fully Synthetic MID SAPS Passenger Car Motor Oil

NORDIC EVOTECH 5W/30 C2 is a high performance fuel saving MID SAPS engine oil based on 100% synthetic technology to be used in gasoline- and diesel engines of the latest generation passenger cars and light vans where a PSA B71 2290 specification is required and suitable for all engines which require an ACEA A5/B5, C2 performance specification.

NORDIC EVOTECH 5W/30 C2 is based on high performance synthetic base oil in combination with a specially selected additive technology to ensure the following properties:

- Excellent thermal and oxidation stability.
- Fuel saving properties.
- Excellent protection against wear, foam and corrosion.
- Low temperature properties, to ensure a smooth cold start.
- Long oil drain interval possible.

NORDIC EVOTECH 5W/30 C2 exceeds the following performance criteria:

API SN/CF
PSA B71 2290

ACEA A1/B1
Renault 0700

ACEA A5/B5

ACEA C2

Typical Analysis

| Properties | Unit | Method | Typical Value |
|---------------------------|--------------------|------------|---------------|
| SAE Grade | | SAE J300 | 5W/30 |
| Density @15°C | kg/m ³ | ASTM D4052 | 854 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D7042 | 65 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D7042 | 11.2 |
| Viscosity Index | | ASTM D2270 | 165 |
| Viscosity CCS @-30°, max. | cP | ASTM D5293 | 6600 |
| Flash Point COC | °C | ASTM D92 | >201 |
| Pour Point | °C | ASTM D97 | -39 |
| Total Base Number | mgKOH/g | ASTM D2896 | 8.1 |
| Sulphated Ash | %Wt | ASTM D874 | 0.79 |

Date Issued: 29-05-2021

Supersedes:

Revision Nr.: 1