

NORDIC EVOTECH 0W/20 VCC

Fully Synthetic Passenger Car Motor Oil

NORDIC EVOTECH 0W/20 VCC is a fuel saving oil based on 100% synthetic technology specially designed for use in Volvo passenger cars with or without turbocharger where Volvo VCC RBS0-2AE is required.

NORDIC EVOTECH 0W/20 VCC can also be used in applications where a ACEA A1/B1 or API: SN is required.

NORDIC EVOTECH 0W/20 VCC is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Protection to wear by cold start.
- Very good low temperature properties.
- Very high thermal- and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High viscosity index.
- Added fuel economy

NORDIC EVOTECH 0W/20 VCC exceeds the following performance criteria:

Volvo VCC RBS0-2AE

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J3000	0W/20
Density @15°C	kg/m ³	ASTM D4052	845
Kin. Viscosity @40°C	mm ² /s	ASTM D7042	47,4
Kin. Viscosity @100°C	mm ² /s	ASTM D7042	9,10
Viscosity Index		ASTM D2270	175
Viscosity CCS @-35°, max.	cP	ASTM D5293	<620
Flash Point COC	°C	ASTM D92	230
Pour Point	°C	ASTM D7346	-45
Total Base Number	mgKOH/g	ASTM D2896	8,0
Sulphated Ash	%Wt	ASTM D874	0,80

Date Issued: 29-05-2021

Supersedes:

Revision Nr.: 1